



Highly efficient, easy to install, robust, long-lasting FLOODLIGHT. PREMIUM class outdoor luminaire.

Aluminium housing, glass cover. Wide selection of optics. For illumination of various areas such as playgrounds, airports, harbours, sports fields, etc.

Made in EU



Product name
EFL-M

Light source
OSRAM / LUMILEDS

Light color
3000 - 6500 K

Color Rendering Index
Ra > 70; 80; 90

Power
From 60W to 200W

Efficacy
Up to 157 lm/W

Optional Sockets
Nema
Zhaga

Interfaces (optional)

- one4all (DALI DT 6, DSI, switchDIM, corridorFUNCTION V2)
- ready2mains (configuration and dimming via mains)
- U6Me2 (configuration of chronoSTEP 2 via mains)

Suitable for mains voltage peaks (burst/surge)
6kV / 10kV

Driver
180 – 264VAC, 176 – 280 VDC

Optics
30, 60, 90 degrees, Asymmetric

Optical cover
Glass, thermally hardened

Material
Heat sink: Cast aluminum, painted

Color
RAL7015, RAL7035, RAL 9005

Operating temperature
-40°C ≤ Ta ≤ +50°C

Life expectancy L/B
L90 B10 by 100000 hrs (Ta = 25°C)

Maintenance
Optical module sealed for life
No internal cleaning required

Installation
Adjustable bracket:
angle -90° +90°

Remarks
Luminaires are ready to install

Size
319 x 432 x 78,5 mm

