



LM OUTPUT  
**Up to 23251 lm**

EFFICACY  
**Up to 165 lm/W**

**Our flagship luminaire with the best quality/price ratio.**

Simple design and high quality components. For indoor industrial lighting: factories, warehouses, terminals, industrial refrigerators, shops, parking lots, food and medical industry, car-care centres – most frequently used applications.

Made in EU



More info on [www.enimighting.com](http://www.enimighting.com)

**Product name**  
 FOCUS 1

**Light color**  
 3000 - 6000 K

**Light source**  
 OSRAM / LUMILEDS

**Color Rendering Index**  
 Ra > 80

**Power**  
 From 80W to 150W

**Efficacy**  
 Up to 165 lm/W

**Interfaces (optional)**  
 DALI / switchDIM / Corridor function / DSI / DALI Device 6

**Integrated sensors (optional)**  
 Preset ON/OFF  
 Remote - DALI (Daylight Harvesting)

**Beam Angle**  
 30 / 60 / 90

**Connection**  
 Supply cable 1,00 m or quick connector

**Material**  
 Heat sink: aluminum extrusion, anodized  
 Mounting bracket: steel

**Color**  
 Grey RAL 7035

**Operating temperature**  
 -25°C ≤ Ta ≤ +50°C

**Lifetime**  
 L90 B10 - 100000 h (Ta = 25°C)

**Maintenance**  
 Optical module sealed for life  
 No internal cleaning required  
 Bracket for suspended mounting

**Remarks**  
 Luminaires are ready to install

**Size**  
 620 x 97 x 70 mm,  
 920 x 97 x 70 mm,  
 1220 x 97 x 70 mm,  
 1420 x 97 x 70 mm

